



EVO2 - 3 GROUPS

CONSISTENT EXTRACTION Patented multiboiler technology, set the temperature with a 0.1° precision and find your sweet spot.

FUNCTIONAL 54 mm-diameter portafilter, ergonomic handgrips, easy and precise milk frothing. DC System compatible (GCS, MCS, OCS).

SUSTAINABILITY Independent groups to switch off unused brewing groups or the boiler. Perfect thermal stability. All parts exposed to water are lead-free (CW510L).

BLACKBOARD EDITION Make it your own! Customize your espresso machine however you like by drawing directly on the blackboard cover - let's play, erase, and keep on creating!

dimensions (w x h x d)	940x510x525 mm
weight	83 kg
power consumption (24h-stand-by)	11,3 kW
max power	6,3 kW
connected load	380/400 V 3 N + T, 50/60 Hz - 220/230 V, 50/60 Hz - 220/230 V 3, 50/60 Hz
boiler capacity	13 l
group head capacity	0,5 l
GCS Grinder Control System	optional
MCS Milk Control System	optional

Version 230 also available

EV02 - 3 GROUPS



ARCTIC WHITE

3 gr 1-MC-EV0DUE-3-W-400



NEBULA BLACK

3 gr 1-MC-EV0DUE-3-N-400




BLACKBOARD

3 gr 1-MC-EV0DUE-3-C-400



DC SYSTEM



MULTIBOILER



COOL TOUCH
(optional)



ENERGY
SAVING



CUSTOM
COLOURS